

Normal	Pro	Deluxe
4 x DIMM, Max. 32GB, DDR3 2200(O.C.)/2133(4 x DIMM, Max. 32GB, DDR3 2200(O.C.)/2133(O.C.)/1866(O.C.)/1600	4 x DIMM, Max. 32GB, DDR3 2200(O.C.)/2133(O.C.)/1866(O.C.)/1600
Integrated Graphics Processor	Integrated Graphics Processor	
2 x PCIe 2.0 x16 (x16 or dual x8) 1 x PCIe 2.0 x16 (x4 mode, black) *1 2 x PCIe x1 2 x PCI	2 x PCIe 2.0 x16 (x16 or dual x8) 1 x PCIe 2.0 x16 (x4 mode, black) *1 2 x PCIe x1 2 x PCI	2 x PCIe 2.0 x16 (x16 or dual x8) 1 x PCIe 2.0 x16 (x4 mode, black) *1 2 x PCIe 2.0 x1 2 x PCI
Intel® Z68 chipset : 2 x SATA 6Gb/s port(s), gray 4 x SATA 3Gb/s port(s), blue Support Raid 0, 1, 5, 10 Support Intel® Smart Response Technology JMicron® JMB362 controller : *2 1 x eSATA 3G port(s), red	Intel® Z68 chipset : 2 x SATA 6Gb/s port(s), gray 4 x SATA 3Gb/s port(s), blue Support Raid 0, 1, 5, 10 Support Intel® Smart Response Technology Marvell® PCIe SATA 6Gb/s controller : *2 2 x SATA 6Gb/s port(s), navy blue JMicron® JMB362 controller : *2 1 x eSATA 3G port(s), red	Intel® Z68 chipset : 2 x SATA 6Gb/s port(s), gray 4 x SATA 3Gb/s port(s), blue Support Raid 0, 1, 5, 10 Support Intel® Smart Response Technology Marvell® PCIe 9128 controller : 2 x SATA 6Gb/s port(s), navy blue JMicron® JMB362 controller : *2 1 x eSATA 3G port(s), red 1 x Power eSATA 3Gb/s port(s), green
Bluetooth V2.1+EDR ASUS BT GO! Utility	Bluetooth V2.1+EDR ASUS BT GO! Utility	Bluetooth V2.1+EDR ASUS BT GO! Utility
- EPU - EPU switch	- EPU - EPU switch	- EPU - EPU switch
1 x Bluetooth module(s) 1 x DVI 1 x D-Sub 1 x HDMI 1 x eSATA 3Gb/s 1 x LAN (RJ45) port(s) 2 x USB 3.0 6 x USB 2.0 1 x Optical S/PDIF out 6 x Audio Jack(s)	1 x Bluetooth module(s) 1 x DVI 1 x D-Sub 1 x HDMI 1 x eSATA 3Gb/s 1 x LAN (RJ45) port(s) 2 x USB 3.0 6 x USB 2.0 1 x Optical S/PDIF out 6 x Audio Jack(s)	1 x PS/2 keyboard/mouse combo port(s) 1 x Bluetooth module(s) 1 x eSATA 3Gb/s 1 x Power eSATA 3Gb/s 1 x IEEE 1394a 2 x LAN (RJ45) port(s) 2 x USB 3.0 8 x USB 2.0 1 x Coaxial S/PDIF out 1 x Optical S/PDIF out 6 x Audio Jack(s) 1 x Clear CMOS button(s)
1 x USB 3.0 connector(s) support(s) additional 2 USB 3.0 port(s) (19-pin, moss green) 3 x USB 2.0 connector(s) support(s) additional 6 USB 2.0 port(s) 2 x SATA 6Gb/s connector(s) 4 x SATA 3Gb/s connector(s) 2 x CPU Fan connector(s) (4-pin) 2 x Chassis Fan connector(s) (1 x 4 -pin, 1 x 3 -pin) 2 x Power Fan connector(s) (3-pin) 1 x S/PDIF out Header(s) 1 x 24-pin EATX Power connector(s) 1 x 8-pin ATX 12V Power connector(s) 1 x Front panel audio connector(s) (AAFP) 1 x System panel(s) (Q-Connector) 1 x MemOK! button(s) 1 x TPU switch(es) 1 x EPU switch(es)	1 x USB 3.0 connector(s) support(s) additional 2 USB 3.0 port(s) (19-pin, moss green) 3 x USB 2.0 connector(s) support(s) additional 6 USB 2.0 port(s) 4 x SATA 6Gb/s connector(s) 4 x SATA 3Gb/s connector(s) 2 x IEEE 1394a connector(s) 2 x CPU Fan connector(s) (4-pin) 2 x Chassis Fan connector(s) (1 x 4 -pin, 1 x 3 -pin) 2 x Power Fan connector(s) (3-pin) 1 x S/PDIF out Header(s) 1 x 24-pin EATX Power connector(s) 1 x 8-pin ATX 12V Power connector(s) 1 x Front panel audio connector(s) (AAFP) 1 x System panel(s) (Q-Connector) 1 x MemOK! button(s) 1 x TPU switch(es) 1 x EPU switch(es)	1 x USB 3.0 connector(s) support(s) additional 2 USB 3.0 port(s) (19-pin, blue) 2 x USB 2.0 connector(s) support(s) additional 4 USB 2.0 port(s) 4 x SATA 6Gb/s connector(s) 4 x SATA 3Gb/s connector(s) 1 x IEEE 1394a connector(s) 1 x CPU Fan connector(s) (4-pin) 2 x Chassis Fan connector(s) (1 x 4 -pin, 1 x 3 -pin) 2 x Power Fan connector(s) (2 x 3 -pin) 1 x S/PDIF out Header(s) 1 x 24-pin EATX Power connector(s) 1 x 8-pin ATX 12V Power connector(s) 1 x Front panel audio connector(s) (AAFP) 1 x System panel(s) (Q-Connector) 1 x MemOK! button(s) 1 x TPU switch(es) 1 x EPU switch(es) 1 x Power-on switch(es) (haben die anderen doch auch?) 1 x Reset switch(es)
User's manual ASUS Q-Shield 2 x Serial ATA 3.0Gb/s cable(s) 2 x Serial ATA 6.0Gb/s cable(s) 1 x SLI bridge(s) 1 x Q-connector(s) (2 in 1)	User's manual ASUS Q-Shield 2 x Serial ATA 3.0Gb/s cable(s) 2 x Serial ATA 6.0Gb/s cable(s) 1 x SLI bridge(s) 1 x Q-connector(s) (2 in 1) 1 x ASUS USB 3.0 Bracket(s)	User's manual ASUS Q-Shield 2 x Serial ATA 3.0Gb/s cable(s) 4 x Serial ATA 6.0Gb/s cable(s) 1 x SLI bridge(s) 1 x Q-connector(s) (2 in 1) 1 x ASUS Front Panel USB 3.0 Box(es)